



- MATERIAL
- 1 – Inner beam : Steel
  - 2 – Inner beam : Steel
  - 3 – Intermediate Beam : Steel
  - 4 – Intermediate Beam : Steel
  - 5 – Bearing  $\phi 10-\phi 8-\phi 6-\phi 4$  : Steel
  - 6 – Ball cages : Steel
  - 7 – End stop : Plastic
- SURFACE FINISH : Zinc plating
- WEIGHT : 25 Kg/m
- OPTIONS :

Dimensions in mm

\* Loads indicated for a pair of slides mounted on the major axis with evenly distributed load.

L	800	850	900	950	1000	1100	1200	1300	1400	1500	1600	1700	1800	1900	2000	—
A	200	250	300	350	400	—	—	—	—	—	—	—	—	—	—	—
B	—	—	—	—	—	150	200	250	300	350	400	450	500	550	600	—
D	1200	1275	1350	1425	1500	1650	1800	1950	2100	2250	2400	2550	2700	2850	3000	—
Load* (Kg)	500	475	450	425	400	375	350	325	300	275	250	225	200	175	150	—
Deflection (mm)	9	10	10	11	12	13	14	15	16	17	18	19	20	21	22	—

E1014

FT 034 – STEEL

08.08.2012

**CHAMBRELAN**  
www.chambrelan.com

BP 995 – 68 Bd Jules DURAND  
76061 LE HAVRE CEDEX – FRANCE  
Tel : +33 (0)2.35.24.62.80 – Fax : +33 (0)2.35.25.02.00  
info@chambrelan.com – www.chambrelan.com

FILIALE : info@profilscope.de – www.profilscope.de

Different slide lengths, extension, surface finish,  $\phi$  and holes centres to customer's requirement.

WE RECOMMEND USE ON THE MAJOR AXIS.  
DO NOT DISMOUNT THE SLIDE !