



— PROFILE :

— MATERIAL

- 1 - Inner beam : Stainless steel
- 2 - Intermediate beam : Stainless steel
- 3 - Intermediate beam : Stainless steel
- 4 - Outer beam : Stainless steel
- 5 - Bearing  $\phi 4-\phi 5$  : Stainless steel
- 6 - Ball retainer : Plastic

— WEIGHT : 5,5 Kg/m

— OPTIONS :

Different slide lengths, extension, surface finish,  
 $\phi$  and holes centres to customer's requirement.

WE RECOMMEND USE ON THE MAJOR AXIS.  
 DO NOT DISMOUNT THE SLIDE !

Dimensions in mm

\* Loads indicated for a pair of slides mounted on the major axis with evenly distributed load.

L	250	300	350	400	450	500	550	600	-	-	-	-	-	-	-
A	235	285	335	385	435	485	-	-	-	-	-	-	-	-	-
B	-	-	-	-	-	-	267,5	292,5	-	-	-	-	-	-	-
C	50	100	150	200	250	300	-	-	-	-	-	-	-	-	-
E	-	-	-	-	-	-	150	175	-	-	-	-	-	-	-
D	375	450	525	600	675	750	825	900	-	-	-	-	-	-	-
Load* (Kg)	47	45	42	40	37	35	32	30	-	-	-	-	-	-	-
Deflection (mm)	3	3	4	4	5	5	6	6	-	-	-	-	-	-	-

ST658  
 FT 070 - STAINLESS STEEL  
 04.06.2008

**CHAMBRELAN**  
[www.chambrelan.com](http://www.chambrelan.com)  
 BP 995 - 68 Bd Jules DURAND  
 76061 LE HAVRE CEDEX - FRANCE  
 Tel : +33 (0)2.35.24.62.80 - Fax : +33 (0)2.35.25.02.00  
 info@chambrelan.com - www.chambrelan.com  
 FILIALE : info@profilscope.de - www.profilscope.de

In a constant effort of improvement, the company reserves the right to modify its products without notice. No contractual information.